

3.1 Input Transactions (Illinois Specific Requirements)

Client-initiated transactions are structured as follows:

Element/Attribute	Required	Length	Specification
OFML	Required	N/A	OFML™ element
OFML.HDR	Required	N/A	Header element
OFML.HDR.ID	Required	10	Message identifier (IL interface identifier) used to identify a message Defaults to OFML.HDR.REF if blank
OFML.HDR.APP	Optional	15	Application Identifier Should always be left blank unless required by the particular implementation
OFML.HDR.DAC	Required	11	Device address code Used when the source of a message can't be determined directly from the communications interface
OFML.HDR.DAT	Required	14	Date/time message generated Format: YYYYMMDDHHMMSS
OFML.HDR.REF	Optional	10	Transaction reference number
OFML.HDR.MKE	Required	7	Message key Per specific transaction Optional TST attribute if set to 'Y' indicates a test transaction
OFML.HDR.ENT	Optional	10	Entering agency Only used when entering agency is included in each transaction.
OFML.HDR.RQR	Optional	30	Requestor Only used when requestor is included in each transaction.
OFML.HDR.USR	Required	12	User ID Only used when user ID is included in each transaction. Standard logon transactions will include the user ID as an MFC element.
OFML.HDR.PWD	Optional	15	Password Only used when user ID and password is included in each transaction. Standard logon transactions will include the password as an MFC element.
OFML.HDR.ORI	Required	9	Source ORI
OFML.HDR.DST	Optional (1-5)	11	One or more destination elements ORI, state code, device mnemonic or broadcast code
OFML.HDR.CTL	Optional	10	NLETS control field Does not include asterisk
OFML.HDR.PASS	Optional	10	Pass through identifier Used to indicate direct message pass through. Value and pass through results are implementation specific.
OFML.HDR.SUM	Optional	80	Transaction Summary Text to summarize contents of message
OFML.TRN	Required	N/A	Transaction element
OFML.TRN DATA ELEMENTS	Required	N/A	Defined in following sections