ISP Standard Table - Craft Grower Organizations

Item		Required	Recommended
Ref. #	Security Component	Standard	Best Practice
6	(Documentation is provided regarding policies and		
	procedures in dealing with security incidents such as	٧	
	robberies, civil unrest, evacuations, weather, and natural	V	
	disaster.)		
21	(Facial recognition at a clarity of 10 feet of distance.)	٧	
21	(Pan/Tilt/Zoom {PTZ} cameras in enhanced security areas		V
	and exterior locations coupled with a fixed view cameras.)		V
21	(Cameras with zoom capability in all places where product		٧
	is located - May be fixed camera with zoom capability.)		V
22	(Overlapping camera coverage with opposing views.)		٧
30	(32" or larger monitors.)		٧
30	(Monitors should be HD and capable of displaying up to 4		٧
	camera views per 20 inches of monitor.)		V
30	(Blackout or privacy capability to shield monitor view from		٧
	visitors.)		V
31	(Monitors placed at secured exterior access points		
	showing what/who is on the other side prior to opening		٧
	door.)		
32	(Completion of a daily monitoring log documenting		
	functionality, quality of picture, and appropriate field of	٧	
	view of all cameras.)		
33	(1080p minimum resolution.)		٧
34	(10 frames per second resolution.)		٧
35	(180- day cloud-based storage with 100% redundancy.)		٧
35	(Redundant server capability allowing for at least 14 days		
	of storage for expansion and backups in the event of		٧
	failed/overloaded servers.)		
41	(Playback ability of live and recorded video is required.)	٧	
41	(Web-portal is password protected requiring a valid SSL		
	certificate and supporting modern SSL encryption cipher	٧	
	suites and compatible with Windows and iOS platforms.)		
41	(Historical remote viewing capability of at least 180 days.)	٧	