

## ISP Standard Table - Infuser Organizations

Item Ref. #	Security Component	Required Standard	Recommended Best Practice
4	<i>(Documentation is provided regarding policies and procedures in dealing with security incidents such as robberies, civil unrest, evacuations, weather, and natural disaster.)</i>	√	
15	<i>(Facial recognition at a clarity of 10 feet of distance.)</i>	√	
15	<i>(Pan/Tilt/Zoom {PTZ} cameras in enhanced security areas and exterior locations coupled with a fixed view cameras.)</i>		√
15	<i>(Cameras with zoom capability in all places where product is located - May be fixed camera with zoom capability.)</i>		√
16	<i>(Overlapping camera coverage with opposing views.)</i>		√
24	<i>(32" or larger monitors.)</i>		√
24	<i>(Monitors should be HD and capable of displaying up to 4 camera views per 20 inches of monitor.)</i>		√
24	<i>(Blackout or privacy capability to shield monitor view from visitors.)</i>		√
25	<i>(Monitors placed at secured exterior access points showing what/who is on the other side prior to opening door.)</i>		√
26	<i>(Completion of a daily monitoring log documenting functionality, quality of picture, and appropriate field of view of all cameras.)</i>	√	
27	<i>(1080p minimum resolution.)</i>		√
28	<i>(10 frames per second resolution.)</i>		√
29	<i>(180- day cloud-based storage with 100% redundancy.)</i>		√
29	<i>(Redundant server capability allowing for at least 14 days of storage for expansion and backups in the event of failed/overloaded servers.)</i>		√
35	<i>(Playback ability of live and recorded video is required.)</i>	√	
35	<i>(Web-portal is password protected requiring a valid SSL certificate and supporting modern SSL encryption cipher suites and compatible with Windows and iOS platforms.)</i>	√	
35	<i>(Historical remote viewing capability of at least 180 days.)</i>	√	